





Model : i-WFR-12



Framed square



Cylindrical inner side




Framed circle



Circular reflecting-ring



Square reflecting ring



- Products fall under 'fixed' and 'rotating' categories.
- The rotating type supports a horizontal rotation of 355° and a vertical rotation of 30°.
- The reflector comes in 6 color options meeting the needs of different occasions and tastes.
- A deep-reflective cup provides an anti-glare effect.
- A die-cast aluminum radiator is used for higher heat-dissipation efficiency.
- CCT—correlated color temperature supports 2700K/3000K/4000K/5000K.
- UGR<9, and Ra≥90, maximum lifespan of 50000h.

Easy and swift installation

Independent design of the product's appearance, Snap-on modular structure, Easy installation and maintenance.

High reflection efficiency

Precise reflector design, Use of electroplating and nano-painting technology, High reflection efficiency, Provides highly efficient light.


Reliable structure, Providing an esthetic lighting effect

Simple, straightforward installation to avoid damage to the ceiling, natural and visually consistent.

Suitable for use in

high-end hotels, villas, mansions; Provides with a comfortable and healthy lighting space.

Accessories:



Specication



Power (Luminaire)	12 W
LED Type	COB
CRI	>90
Size	W86 * H104mm
Lumen (Luminaire)	881 lm
Input Volt	AC 220-240V
Color Temperature	2700K,3000K,4000K,5000K
Beam Angle	10° 15° 24° 38° 50°
Driver	Dimmable 0-100% Trailing Edge and Leading Edge
LED Life	50000h
IP Rating	IP 20
LEN	Honeycomb Louver
Enclosure Material	Die-cast aluminum
Accessories	White trim/ Mirror reactor

